



RX-W32

A large-format, featured-packed 32" widescreen display protected by NeoV™ Optical Glass and a durable metal frame for serious security environments.

Introducing the RX-W32, a large-format hard glass display designed for the serious surveillance centre. A high resolution 32" screen, image-enhancing 3D Comb Filter / 3D Deinterlace technology, and versatile Picture-in-Picture (PIP) options provide sharp images and features security professionals need. Ultra-low power consumption significantly improves efficiency for cost-savings the best 24/7 security environments demand. All this, plus protective NeoV™ Optical Glass and sturdy metal casing, makes the RX-W32 the most robust and advanced display choice for maximum surveillance performance.

- > 1366 x 768 WXGA resolution
- > 3000:1 contrast ratio
- > NeoV™ Optical Glass
- > PIP, PBP and VOV functions
- > 3D Comb Filter / 3D Deinterlace
- > Ultra-low power consumption (≤ 98W)
- > Multiple video inputs (BNC in x2, BNC out x2)
- > NTSC/PAL video system support
- > Quick signal-switching time
- > Built-in speakers
- > IR remote control
- > Slim border & bezel
- > Durable metal housing
- > Control key lock function
- > VESA standard wall mount




NeoV™ Optical Glass - The most
trusted hard glass protection available.
Only on AG Neovo displays

RX-W32

Specifications

RX-W32

Panel	Panel Type	TFT LCD
	Panel Size	32"
	Max. Resolution	WXGA 1366 x 768
	Pixel Pitch	0.51075 mm
	Brightness	450 cd/m ² (Typical)
	Contrast Ratio	3000:1 (Typical)
	Viewing Angle (H/V)	178°/178° (Typical)
	Display Colour	16.7M
	Response Time	6.5 ms (GTG)
	Panel Life Time	50,000 hrs
Frequency (H/V)		H: 31 kHz - 80 kHz V: 50 Hz - 85 Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	CVBS	BNC x 2
	S-Video	4-Pin mini DIN
	Component (YPbPr)	RCA x 2
Output	CVBS	BNC x 2
	S-Video	4-Pin mini DIN
Audio	Audio In	1 x stereo audio in for PC (audio jack, 3.5 Ø) 1 x stereo audio in for CVBS (RCA) 1 x stereo audio in for S-Video (RCA) 2 x stereo audio in for YPbPr (RCA)
	Audio Out Speaker	1 x stereo audio out for CVBS (RCA) 2W x 2
Power	DC output	12V / 350 mA, DC jack 2.5 Ø
	Power Consumption	100 - 240V, 50 - 60 Hz 98W (On) / 10W (Off)
NeoV™ Optical Glass	Thickness	3.0 mm (0.18")
	Reflection Rate	< 1%
	Transmission Rate	> 96%
	Coating Hardness	> 9H
Operating Conditions	Temperature	0 °C ~ 40 °C
	Humidity	10% ~ 85%
Storage Conditions	Temperature	-20 °C ~ 60 °C
	Humidity	10% ~ 95%
Mounting	VESA FPMPI	Yes (400 x 200 mm)
Dimensions	Without Base (W x H x D)	788 x 478 x 101 mm (31" x 18.8" x 4")
	With Base (W x H x D)	788 x 541 x 170 mm (31" x 21.3" x 6.7")
Weight	Without Base	16.8 kg (37.0 lbs)
	With Base	18.3 kg (40.3 lbs)
Accessories	Supplied	User manual, 15-Pin VGA cable, 24-Pin DVI cable, power cord, audio cable, IR remote control, warranty card



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



Viewing versatility with Picture-in-Picture (PIP), Picture-by-Picture (PBP) and Video-on-Video (VOV)



Multiple video inputs (VGA, DVI, dual BNC, S-Video and Component) allow for effortless system integration



Durable metal casing for enhanced strength and secure mounting